

Ceph - Bug #12570

common/Thread:pthread_attr_destroy(thread_attr) when done with it

08/03/2015 01:58 PM - qiankun zheng

Status:	Resolved	Start date:	08/03/2015
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:		Spent time:	0.00 hour
Source:	other	Reviewed:	
Tags:		Affected Versions:	
Backport:	firefly, hammer	ceph-qa-suite:	
Regression:	No	Pull request ID:	
Severity:	3 - minor		
Description			
when a thread attributes object is no longer required, it should be destroyed using the pthread_attr_destroy() function. Destroying a thread attributes object has no effect on threads that were created using that object. However,does not call pthread_attr_destroy() function to remove the initialization in the program.			
Related issues:			
Copied to Ceph - Backport #13040: common/Thread:pthread_attr_destroy(thread_a...		Resolved	
Copied to Ceph - Backport #13041: common/Thread:pthread_attr_destroy(thread_a...		Resolved	08/03/2015

Associated revisions

Revision 9471bb83 - 08/07/2015 02:55 AM - qiankun zheng

Common/Thread: pthread_attr_destroy(thread_attr) when done with it

When a thread attributes object is no longer required, it should be destroyed using the pthread_attr_destroy() function. Destroying a thread attributes object has no effect on threads that were created using that object.

Fixes: #12570

Signed-off-by: zqkqkz zheng.qiankun@h3c.com

Revision f1271eae - 10/02/2015 02:00 PM - qiankun zheng

Common/Thread: pthread_attr_destroy(thread_attr) when done with it

When a thread attributes object is no longer required, it should be destroyed using the pthread_attr_destroy() function. Destroying a thread attributes object has no effect on threads that were created using that object.

Fixes: #12570

Signed-off-by: zqkqkz zheng.qiankun@h3c.com

(cherry picked from commit 9471bb838a420ef5f439191d87e5388fecccb9e6)

Revision 81bb6dd7 - 10/20/2015 09:37 AM - qiankun zheng

Common/Thread: pthread_attr_destroy(thread_attr) when done with it

When a thread attributes object is no longer required, it should be destroyed using the pthread_attr_destroy() function. Destroying a thread attributes object has no effect on threads that were created using that object.

Fixes: #12570

Signed-off-by: zqkqkz zheng.qiankun@h3c.com

History

#1 - 08/04/2015 07:25 AM - qiankun zheng

<https://github.com/ceph/ceph/pull/5433>

#2 - 08/07/2015 06:44 PM - Kefu Chai

- Status changed from New to Need Review
- Backport set to firefly, hammer

<https://github.com/ceph/ceph/pull/5433>

#3 - 09/08/2015 02:55 PM - Sage Weil

- Status changed from Need Review to Resolved

#4 - 09/08/2015 02:57 PM - Sage Weil

- Status changed from Resolved to Pending Backport

#5 - 11/10/2015 11:15 AM - Loic Dachary

- Status changed from Pending Backport to Resolved