

rbd - Feature #1790

rbd: have a way of establishing configured mappings at boot time

12/06/2011 11:10 AM - Anonymous

Status: Resolved	% Done: 0%
Priority: Normal	Spent time: 1.00 hour
Assignee:	
Category:	
Target version:	
Source:	Reviewed:
Tags:	Affected Versions:
Backport:	Pull request ID:
Description	
<p>We need to be careful about the config format, to make automatic editing easy (think Chef).</p> <p>First draft:</p> <p>/etc/ceph/rbd.d/NAME.conf is used as ceph.conf to map image called NAME. You can drop in multiple .conf files in that directory.</p> <p>Two major use cases:</p> <p>1) In -s /etc/ceph/ceph.conf /etc/ceph/rbd.d/foo.conf maps image "foo" at boot time with the main ceph.conf settings, with the keyrings configured there</p> <p>2) install -m0600 appropriate-keyring /etc/ceph/rbd.d/bar.keyring cat >>/etc/ceph/rbd.d/bar.conf <<EOF [global] ... keyring = bar.keyring EOF</p>	

History

#1 - 12/06/2011 11:56 PM - Wido den Hollander

What if your image is not in the pool "rbd" ?

I was thinking about a 'rbdtab' file:

#Monitor(s)	#Args	#Pool	#Image
192.168.1.6	id=admin,secret=/etc/ceph/secret	rbd	alpha
192.168.1.6	id=admin,secret=/etc/ceph/secret	rbd2	beta

Wouldn't that be easier?

#2 - 12/07/2011 09:27 AM - Anonymous

Single-file configuration is more annoying to handle with automated tools, file-per-device gives you good atomicity on manipulating the configuration.

Your point about pools is very good. I originally thought of putting "[rbd foo]" etc inside the config file, but I'm really hesitant to add special-purpose, more dynamic, fields/sections into the config file, and feel this is on a different level from ceph.conf anyway.

Perhaps /etc/ceph/rbd.d/ANYTHINGUNIQUEHERE.conf with contents like

```
image = NAME # maybe leave out to take from name of conf file
pool = notrbd # leave out for default "rbd"
id = cephkeythatcanmaprbd # leave out for default "admin"
config = /etc/ceph/non-default-ceph.conf # leave out for default
```

#3 - 06/29/2012 11:48 AM - Sage Weil

- *Project changed from Ceph to rbd*

#4 - 06/25/2013 01:05 AM - Loic Dachary

For the record : [Add rc script for rbd map/unmap](#)

#5 - 09/27/2013 01:15 PM - Josh Durgin

- *Status changed from New to Resolved*

commit:a4ddf704868832e119d7949e96fe35ab1920f06a