

Ceph - Bug #4940

rbid: set mapping read-only flag in rbd\_add()

05/08/2013 06:28 AM - Alex Elder

<b>Status:</b>	Resolved	<b>% Done:</b>	0%
<b>Priority:</b>	Normal	<b>Spent time:</b>	0.00 hour
<b>Assignee:</b>	Alex Elder		
<b>Category:</b>			
<b>Target version:</b>	v0.62b		
<b>Source:</b>	other	<b>Affected Versions:</b>	
<b>Tags:</b>		<b>ceph-qa-suite:</b>	
<b>Backport:</b>		<b>Pull request ID:</b>	
<b>Regression:</b>	No	<b>Crash signature (v1):</b>	
<b>Severity:</b>	3 - minor	<b>Crash signature (v2):</b>	
<b>Reviewed:</b>			

**Description**

The rbd\_dev->mapping field for a parent image is not meaningful. Since rbd\_image\_probe() is used both for images being mapped and their parents, it doesn't make sense to set that flag in that function.

So move the setting of the mapping.read\_only flag out of rbd\_dev\_image\_probe() and into rbd\_add() instead.

Signed-off-by: Alex Elder <[elder@inktank.com](mailto:elder@inktank.com)>

History

#1 - 05/08/2013 03:33 PM - Alex Elder

- Status changed from In Progress to Fix Under Review

The following has been posted for review. It is one of the patches available in the "review/wip-rbd-cleanup-2" branch of the ceph-client git repository.

[PATCH 3/5] rbd: set mapping read-only flag in rbd\_add()

#2 - 05/08/2013 06:19 PM - Alex Elder

- Status changed from Fix Under Review to Resolved

The following has been committed to the ceph-client "testing-next" branch.

7ce4eef rbd: set mapping read-only flag in rbd\_add()