

Ceph - Bug #1113

rdir is not set correctly for the mons

05/26/2011 09:45 AM - Bernard Grymonpon

Status: Resolved	% Done: 0%
Priority: Normal	Spent time: 0.00 hour
Assignee:	
Category:	
Target version: v0.29	
Source:	Reviewed:
Tags:	Affected Versions:
Backport:	ceph-qa-suite:
Regression: No	Pull request ID:
Severity: 3 - minor	Crash signature:
Description In mkcephfs, rdir is used to keep the config in for remote hosts, and dir is used for localhost. However, when bootstrapping the mon on the local machine, rdir is defined incorrectly with the remote dir, even for the localhost. Verified in master, src/mkcephfs.in, and a quick fix is added, which worked for me.	

Associated revisions

Revision e9eeb161 - 05/26/2011 05:19 PM - Sage Weil

mkcephfs: set rdir for local mon setup

Fixes: #1113

Reported-by: Bernard Grymonpon <bernard@openminds.be>

Signed-off-by: Sage Weil <sage@newdream.net>

History

#1 - 05/26/2011 10:20 AM - Sage Weil

- Status changed from New to Resolved

- Target version set to v0.29

Fixed in stable branch. BTW in the future please add a Signed-off-by to your patches... see SubmittingPatches file in ceph.git.

Thanks!

Files

set_rdir_for_localhost_to_dir.diff

346 Bytes

05/26/2011

Bernard Grymonpon