

Linux kernel client - Fix #11234

rbd does many requests to the header on start-up

03/25/2015 04:26 PM - Josh Durgin

Status:	Need Review	Start date:	03/25/2015
Priority:	Normal	Due date:	
Assignee:	Douglas Fuller	% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:	sprint	Spent time:	0.00 hour
Source:	other	Affected Versions:	
Tags:		ceph-qa-suite:	
Backport:		Crash signature:	
Reviewed:			
Description			
This can be collapsed into a few requests, like cls_client::[im]mutable_metadata() in userspace.			
Multiple cls ops can be packed into one rados request.			
Related issues:			
Related to Linux kernel client - Feature #10933: refactor krbd map/unmap paths			New 02/24/2015

History

#1 - 04/07/2015 04:24 PM - Douglas Fuller

- Assignee set to Douglas Fuller

#2 - 04/14/2015 04:09 PM - Douglas Fuller

- Status changed from New to In Progress

#3 - 04/14/2015 04:09 PM - Douglas Fuller

- Target version set to sprint

#4 - 04/14/2015 04:10 PM - Josh Durgin

- Tracker changed from Bug to Fix

#5 - 04/28/2015 09:08 PM - Josh Durgin

- Status changed from In Progress to Need Review