

Calamari - Bug #11559

Error with calamari_osd_location

05/07/2015 11:13 AM - Yannick Van Styvendael

Status:	Resolved	% Done:	0%
Priority:	High	Spent time:	0.00 hour
Assignee:	Christina Meno	Reviewed:	
Category:	Backend (services)	Affected Versions:	1.3-rc1
Target version:	1.3-rc1	ceph-qa-suite:	ceph-deploy, rados, rgw, upgrade/hammer
Source:	other	Crash signature (v1):	
Tags:		Crash signature (v2):	
Backport:			
Regression:	No		
Severity:	1 - critical		
Description			
Hi,			
I installed successfully the Calamari server running on an Ubuntu 12.04.5. The ceph cluster is installed on a Red Hat 6.3.			
I installed the salt and diamond stuff. When a restart the ceph services, I got this message :			
ERROR:calamari_osd_location:Error 2 running ceph config-key get:'Error ENOENT: error obtaining 'daemon-private/osd.0/v1/calamari/osd_crush_location': (2) No such file or directory'			
ERROR:calamari_osd_location:Error 2 running ceph config-key get:'Error ENOENT: error obtaining 'daemon-private/osd.0/v1/calamari/osd_crush_location': (2) No such file or directory'			
I also receive this error when I run the command /usr/bin/calamari-crush-location			
[root@UAT1 ~]# /usr/bin/calamari-crush-location --id 0 --type osd			
ERROR:calamari_osd_location:Error 2 running ceph config-key get:'Error ENOENT: error obtaining 'daemon-private/osd.0/v1/calamari/osd_crush_location': (2) No such file or directory'			
ERROR:calamari_osd_location:Error 2 running ceph config-key get:'Error ENOENT: error obtaining 'daemon-private/osd.0/v1/calamari/osd_crush_location': (2) No such file or directory'			
host=UAT1			
So on Calamari WebApp, I do not have any cluster detected.			
1 Ceph servers are connected to Calamari, but no Ceph cluster has been created yet. Please use ceph-deploy to create a cluster; please see the Inktank Ceph Enterprise			

Associated revisions

Revision 7227ee4b - 05/26/2015 05:13 PM - Gregory Meno

calamari: fix getting previous CRUSH location

Fixes #11559

Signed-off-by: Gregory Meno <gmeno@redhat.com>

Revision 78628542 - 08/19/2015 04:54 PM - Gregory Meno

calamari: fix getting previous CRUSH location

Fixes #11559

Signed-off-by: Gregory Meno <gmeno@redhat.com>

(cherry picked from commit 7227ee4be9e345a4e9acdba1ff867b31e13f2414)

History

#1 - 05/15/2015 10:59 PM - Christina Meno

I agree this is a serious issue. I will look into it.
Would you please tell me a little more about your setup.

Is this a new calamari install or an upgrade?
Can you tell me what version of ceph your cluster is running?

#2 - 05/16/2015 08:27 PM - Yannick Van Styvendael

Hi,

The Calamari install is a new one.
The Ceph cluster is running latest version (Hammer - 0.94.1)

Kind regards,
yannick

#3 - 05/22/2015 07:28 PM - Christina Meno

reproduced. I will begin a fix now.
[ubuntu@vpm041 ~]\$ sudo service ceph start osd === osd.0 ===
Starting Ceph osd.0 on vpm041...already running === osd.0 ===
Starting Ceph osd.0 on vpm041...already running
[ubuntu@vpm041 ~]\$ sudo service ceph restart osd === osd.0 === === osd.0 ===
Stopping Ceph osd.0 on vpm041...kill 24563...kill 24563...done === osd.0 ===
ERROR:calamari_osd_location:Error 2 running ceph config-key get:'Error ENOENT: error obtaining
'daemon-private/osd.0/v1/calamari/osd_crush_location': (2) No such file or directory'
ERROR:calamari_osd_location:Error 2 running ceph config-key get:'Error ENOENT: error obtaining
'daemon-private/osd.0/v1/calamari/osd_crush_location': (2) No such file or directory'
create-or-move updated item name 'osd.0' weight 0.19 at location {host=vpm041} to crush map
Starting Ceph osd.0 on vpm041...
Running as unit run-6296.service.
[ubuntu@vpm041 ~]\$

#4 - 05/25/2015 07:58 PM - Christina Meno

- Category set to Backend (services)
- Status changed from New to In Progress
- Assignee set to Christina Meno
- Target version set to 1.3-rc1

#5 - 06/01/2015 06:37 PM - Christina Meno

- Status changed from In Progress to Resolved