

Ceph - Bug #21982

osdc/Objecter: objecter op_send_bytes perf counter always 0

10/31/2017 06:04 AM - Honggang Yang

Status:	Resolved	Start date:	10/31/2017
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	Objecter	Estimated time:	0.00 hour
Target version:		Spent time:	0.00 hour
Source:	Development	Reviewed:	
Tags:		Affected Versions:	
Backport:	luminous	ceph-qa-suite:	
Regression:	No	Pull request ID:	
Severity:	3 - minor		
Description			
<pre># ./bin/ceph daemon /tmp/ceph-asok.mMaOCs/client.rgw.32135.asok --conf ceph.conf perf dump grep o p_send *** DEVELOPER MODE: setting PATH, PYTHONPATH and LD_LIBRARY_PATH *** "op_send": 38426, "op_send_bytes": 0, "poolop_send": 0,</pre>			
Related issues:			
Copied to Ceph - Backport #22189: luminous: osdc/Objecter: objecter op_send_b...			Resolved

History

#1 - 11/08/2017 08:39 AM - jianpeng ma

This because at this time, MOSDOP don't encode_payload. So m->get_data.length() = 0.
<https://github.com/ceph/ceph/pull/18810> can fix this .

#2 - 11/20/2017 06:40 AM - Kefu Chai

- Status changed from New to Pending Backport
- Backport set to luminous

#3 - 11/20/2017 11:05 AM - Nathan Cutler

- Copied to Backport #22189: luminous: osdc/Objecter: objecter op_send_bytes perf counter always 0 added

#4 - 02/01/2018 11:25 PM - Nathan Cutler

- Status changed from Pending Backport to Resolved