

ceph-volume - Bug #24504

prevent zap/destroy on dm devices

06/12/2018 10:39 AM - Alfredo Deza

Status: Resolved	% Done: 0%
Priority: Normal	
Assignee:	
Category:	
Target version:	
Source:	Affected Versions:
Tags:	ceph-qa-suite:
Backport:	Pull request ID:
Regression: No	Crash signature (v1):
Severity: 3 - minor	Crash signature (v2):
Reviewed:	

Description

Otherwise, the issue is not really clear from the errors:

```
root@polstor01:/home/urzadmin# ceph-volume lvm zap --destroy /dev/dm-0
--> Zapping: /dev/dm-0
Running command: /sbin/cryptsetup status /dev/mapper/
  stdout: /dev/mapper/ is inactive.
--> Skipping --destroy because no associated physical volumes are found for /dev/dm-0
Running command: wipefs --all /dev/dm-0
  stderr: wipefs: error: /dev/dm-0: probing initialization failed: Device or resource busy
--> RuntimeError: command returned non-zero exit status: 1
```

History

#1 - 07/10/2018 01:22 PM - Andrew Schoen

- Status changed from New to Resolved

<https://github.com/ceph/ceph/pull/22764>

#2 - 08/03/2018 12:03 PM - Alfredo Deza

Mimic PR <https://github.com/ceph/ceph/pull/22965>

Luminous PR <https://github.com/ceph/ceph/pull/23374>