

rgw - Bug #39000

rgw: beast endpoint doesn't set a default port

03/28/2019 12:40 PM - Abhishek Lekshmanan

Status: Resolved	% Done: 0%
Priority: Normal	Spent time: 0.00 hour
Assignee: Abhishek Lekshmanan	
Category:	
Target version:	
Source:	Affected Versions:
Tags: beast	ceph-qa-suite:
Backport: nautilus, mimic	Pull request ID: 27242
Regression: No	Crash signature (v1):
Severity: 3 - minor	Crash signature (v2):
Reviewed:	
Description if endpoint is specified without a trailing port, we don't seem to set this to the default port. Also specifying port= argument always binds a ipv4 address with the port, so a ipv6 endpoint(without a port) and a port argument will bind a ipv4 with port argument and ipv6 without a port.	
Related issues:	
Copied to rgw - Backport #39048: nautilus: rgw: beast endpoint doesn't set a ...	Resolved
Copied to rgw - Backport #39049: mimic: rgw: beast endpoint doesn't set a def...	Resolved

History

#1 - 03/28/2019 05:38 PM - Abhishek Lekshmanan

- Status changed from New to In Progress
- Assignee set to Abhishek Lekshmanan
- Tags set to beast
- Pull request ID set to 27242

#2 - 03/29/2019 05:22 PM - Casey Bodley

- Status changed from In Progress to Pending Backport

#3 - 03/30/2019 08:19 AM - Nathan Cutler

- Copied to Backport #39048: nautilus: rgw: beast endpoint doesn't set a default port added

#4 - 03/30/2019 08:19 AM - Nathan Cutler

- Copied to Backport #39049: mimic: rgw: beast endpoint doesn't set a default port added

#5 - 05/31/2019 12:44 PM - Nathan Cutler

- Status changed from Pending Backport to Resolved