

mgr - Feature #39093

mgr/orchestrator: add `ceph orchestrator wait`

04/03/2019 01:37 PM - Sebastian Wagner

| | | | |
|--|------------------|---------------------------|------------|
| Status: | Need Review | Start date: | 04/03/2019 |
| Priority: | Normal | Due date: | |
| Assignee: | Sebastian Wagner | % Done: | 0% |
| Category: | orchestrator | Estimated time: | 0.00 hour |
| Target version: | | Reviewed: | |
| Source: | Development | Affected Versions: | |
| Tags: | | Pull request ID: | 26565 |
| Backport: | nautilus | | |
| Description | | | |
| <p>Add ceph orchestrator wait that waits for unfinished completions Replace self._orchestrator_wait([completion]) with yield Signed-off-by: Sebastian Wagner sebastian.wagner@suse.com</p> <p>The cli then looks like so:</p> <pre>\$ ceph 'orchestrator' service ls --wait=false queued. \$ ceph 'orchestrator' osd create localhost:/dev/xxx --wait=false queued. \$ ceph orchestrator wait <read op> None ceph-mgr localhost None None None None ceph-mgr localhost None None None None ceph-mgr localhost None None None None ceph-mon localhost None None None None ceph-mon localhost None None None None ceph-mon localhost None None None None ceph-osd localhost None None None None ceph-osd localhost None None None None ceph-osd localhost None None None None ceph-osd localhost None None None create_osds, args=(<orchestrator.DriveGroupSpec object at 0x7f264d4b01d0>, ['localhost']), kwargs={} None</pre> | | | |