

## rgw - Bug #40118

### rgw\_file: include tenant when hashing bucket names

06/03/2019 09:03 PM - Matt Benjamin

<b>Status:</b> Resolved	<b>% Done:</b> 0%
<b>Priority:</b> Normal	<b>Spent time:</b> 0.00 hour
<b>Assignee:</b> Matt Benjamin	
<b>Category:</b>	
<b>Target version:</b>	
<b>Source:</b>	<b>Affected Versions:</b>
<b>Tags:</b>	<b>ceph-qa-suite:</b>
<b>Backport:</b> nautilus,mimic,luminous	<b>Pull request ID:</b> 28370
<b>Regression:</b> No	<b>Crash signature (v1):</b>
<b>Severity:</b> 2 - major	<b>Crash signature (v2):</b>
<b>Reviewed:</b>	
<b>Description</b> Paths different only by tenant were not distinguished in NFS RGW's handle cache. I propose to address this by including tenant-id in the hash of bucket name, preventing identical segments from hashing to the same file id.	
<b>Related issues:</b>	
Copied to rgw - Backport #40224: luminous: rgw_file: include tenant when hash...	<b>Rejected</b>
Copied to rgw - Backport #40225: mimic: rgw_file: include tenant when hashing...	<b>Resolved</b>
Copied to rgw - Backport #40226: nautilus: rgw_file: include tenant when hash...	<b>Resolved</b>

#### History

##### #1 - 06/03/2019 09:18 PM - Matt Benjamin

- Pull request ID set to 28370

##### #2 - 06/06/2019 01:05 PM - Matt Benjamin

- Status changed from Fix Under Review to Pending Backport

##### #3 - 06/10/2019 10:27 AM - Nathan Cutler

- Copied to Backport #40224: luminous: rgw\_file: include tenant when hashing bucket names added

##### #4 - 06/10/2019 10:27 AM - Nathan Cutler

- Copied to Backport #40225: mimic: rgw\_file: include tenant when hashing bucket names added

##### #5 - 06/10/2019 10:27 AM - Nathan Cutler

- Copied to Backport #40226: nautilus: rgw\_file: include tenant when hashing bucket names added

##### #6 - 01/27/2021 07:11 PM - Nathan Cutler

- Status changed from Pending Backport to Resolved

While running with --resolve-parent, the script "backport-create-issue" noticed that all backports of this issue are in status "Resolved" or "Rejected".