

## Orchestrator - Feature #43962

### cephadm: Make mgr/cephadm declarative

02/04/2020 04:44 PM - Sebastian Wagner

<b>Status:</b> Resolved	<b>% Done:</b> 100%
<b>Priority:</b> Normal	
<b>Assignee:</b> Joshua Schmid	
<b>Category:</b> cephadm	
<b>Target version:</b>	
<b>Source:</b>	<b>Reviewed:</b>
<b>Tags:</b>	<b>Affected Versions:</b>
<b>Backport:</b>	<b>Pull request ID:</b>
<b>Description</b> Make mgr/cephadm more like rook <ul style="list-style-type: none"><li>• Make use of labels</li><li>• let mgr/cephadm read the labels + compare it to reality</li><li>• right now, we have a very simple scheduler</li><li>• Maybe ceph cephadm push-config -i config.yaml</li></ul> E.g the RGW config yaml should be stored in the persistent mon store in order to make it possible to simply deploy new RGWs without specifying the full config every time.	
<b>Subtasks:</b> Feature # 44205: cephadm: push/apply config.yaml	
<b>Resolved</b>	

#### History

#1 - 02/04/2020 04:53 PM - Sebastian Wagner

- Description updated

#2 - 02/19/2020 10:27 AM - Joshua Schmid

- Assignee set to Joshua Schmid

#3 - 03/09/2020 09:52 PM - Sage Weil

- Status changed from New to Resolved