

Orchestrator - Bug #44079

cephadm: ModuleNotFoundError: No module named 'distutils.spawn'

02/11/2020 04:24 PM - Sebastian Wagner

Status:	Resolved	% Done:	0%
Priority:	Normal		
Assignee:			
Category:	cephadm (binary)		
Target version:			
Source:		Reviewed:	
Tags:		Affected Versions:	
Backport:		ceph-qa-suite:	
Regression:	No	Pull request ID:	33374
Severity:	3 - minor	Crash signature:	

Description

As cephadm is supposed to not require any Python dependencies, we might need to document this:

```
sebastian@host $ vagrant init generic/ubuntu1804
sebastian@host $ vagrant up --provider=libvirt
Bringing machine 'default' up with 'libvirt' provider...
==> default: Creating image (snapshot of base box volume).
==> default: Creating domain with the following settings...
==> default: -- Name:                vagrant-ubuntu_default
==> default: -- Domain type:             kvm
==> default: -- Cpus:                       2
==> default:
==> default: -- Feature:                    acpi
==> default: -- Feature:                    apic
==> default: -- Feature:                    pae
==> default: -- Memory:                     2048M
==> default: -- Management MAC:
==> default: -- Loader:
==> default: -- Base box:                   generic/ubuntu1804
==> default: -- Storage pool:              default
==> default: -- Image:                     /var/lib/libvirt/images/vagrant-ubuntu_default.img (32G)
==> default: -- Volume Cache:              default
==> default: -- Kernel:
==> default: -- Initrd:
==> default: -- Graphics Type:             vnc
==> default: -- Graphics Port:             -1
==> default: -- Graphics IP:               127.0.0.1
==> default: -- Graphics Password:         Not defined
==> default: -- Video Type:                cirrus
==> default: -- Video VRAM:                256
==> default: -- Sound Type:
==> default: -- Keymap:                     en-us
==> default: -- TPM Path:
==> default: -- INPUT:                      type=mouse, bus=ps2
==> default: Creating shared folders metadata...
==> default: Starting domain.
==> default: Waiting for domain to get an IP address...
==> default: Waiting for SSH to become available...
default:
default: Vagrant insecure key detected. Vagrant will automatically replace
default: this with a newly generated keypair for better security.
default:
default: Inserting generated public key within guest...
default: Removing insecure key from the guest if it's present...
default: Key inserted! Disconnecting and reconnecting using new SSH key...
```

```
==> default: Configuring and enabling network interfaces...
sebastian@host $ vagrant ssh
vagrant@ubuntu1804:~$ sudo su -
root@ubuntu1804:~# curl --silent --remote-name --location https://github.com/ceph/ceph/raw/master/
src/cephadm/cephadm
root@ubuntu1804:~# chmod +x cephadm
root@ubuntu1804:~# ./cephadm --image ceph/daemon-base:latest-master-devel --image pcuzner/ceph-gra
fana-el8:latest deploy --name grafana.a --fsid 00000000-0000-0000-0000-0000deadbeef --config-json
-
Traceback (most recent call last):
  File "./cephadm", line 59, in <module>
    from distutils.spawn import find_executable
ModuleNotFoundError: No module named 'distutils.spawn'
```

History

#1 - 02/20/2020 01:57 PM - Sebastian Wagner

- Status changed from New to Resolved
- Pull request ID set to 33374