

CephFS - Bug #50010

qa/cephfs: get_key_from_keyfile() return None when key is not found in keyfile

03/26/2021 11:39 AM - Rishabh Dave

| | | | |
|---|------------------|------------------------------|-------|
| Status: | Fix Under Review | % Done: | 0% |
| Priority: | Normal | | |
| Assignee: | Rishabh Dave | | |
| Category: | | | |
| Target version: | v17.0.0 | | |
| Source: | | ceph-qa-suite: | |
| Tags: | | Component(FS): | |
| Backport: | | Labels (FS): | |
| Regression: | No | Pull request ID: | 40434 |
| Severity: | 3 - minor | Crash signature (v1): | |
| Reviewed: | | Crash signature (v2): | |
| Affected Versions: | | | |
| Description | | | |
| Absence of key in a keyring file is an odd and exceptional situation. Therefore, CephFSMount.get_key_from_keyfile() should raise an exception instead of ignoring the situation and returning None. | | | |

History

#1 - 03/29/2021 01:46 PM - Patrick Donnelly

- Assignee set to Rishabh Dave
- Target version set to v17.0.0

#2 - 04/28/2021 05:33 AM - Rishabh Dave

- Status changed from In Progress to Fix Under Review
- Pull request ID set to 40434