

## Ceph - Bug #754

### mkfs script should clean up its entries in /tmp, and use TMPDIR

02/01/2011 05:09 PM - Colin McCabe

|   |              |                           |           |
|---|--------------|---------------------------|-----------|
| <b>Status:</b>  | Resolved     | <b>% Done:</b>            | 0%        |
| <b>Priority:</b>  | Low          | <b>Spent time:</b>        | 0.00 hour |
| <b>Assignee:</b>  | Colin McCabe |                           |           |
| <b>Category:</b>  |              |                           |           |
| <b>Target version:</b>  | v0.25        |                           |           |
| <b>Source:</b>  |              | <b>Reviewed:</b>          |           |
| <b>Tags:</b>  |              | <b>Affected Versions:</b> |           |
| <b>Backport:</b>  |              | <b>ceph-qa-suite:</b>     |           |
| <b>Regression:</b>  | No           | <b>Pull request ID:</b>   |           |
| <b>Severity:</b>  | 3 - minor    | <b>Crash signature:</b>   |           |
| <b>Description</b>  |              |                           |           |
| Our mkfs shell script creates stuff in /tmp and doesn't clean it up. Should use "trap" to ensure that this stuff gets cleaned up. Also, we should use ENV[TMPDIR] rather than blindly assuming that /tmp is where to put stuff. I guess mkdtmp/mkstmp handles that for you. |              |                           |           |

#### History

##### #1 - 02/03/2011 10:25 AM - Sage Weil

- Assignee set to Colin McCabe

##### #2 - 02/03/2011 10:25 AM - Sage Weil

- Target version set to v0.25

##### #3 - 02/07/2011 05:18 PM - Colin McCabe

- Status changed from New to Resolved

implemented by [09c38e8edadb3a5bf470ff9b0409172e0c61e012](#) and [aa8a25592f442ab640708115e144e6b8d95cb664](#)